


Table de cuisson Ognidove



Freestanding

Code: 5021 240



DETAILS

Coloring Black

Edge/Installation Type Freestanding

Material AISI 304 stainless steel + ceramic glass

Texture Foster brushed

Supply 230V - 50.60 Hz

Dimensions 380x520 mm

Base size 40cm

Heating element single zone

Notes: Sharp edges
Included: Schuko electric plug

Total power	3.000 W
Centre	Ø 250 mm-2.300 (3.000)* W
Power settings	9 power settings per zone + Powerboost
Safety	Safety equipment
Type	Induction Hob
Type of commands	Touch Control


FEATURES

End-of-cooking programming	All operations are programmed by means of the touch-control on the glass itself. Each cooking plate is capable of independent programming, and thus the possibility to set different cooking times.
Pot detector	All induction cooker hobs detect the pot resting on them, but they also calculate the area they cover. This system allows the energy to be used even more efficiently. Moreover, the plates switch off automatically when the pot is removed.
Powerboost	Booster function provides increased power to the selected plate. In particular, when the Booster is activated, the plate works for ten minutes at a very high power that allows to heat quickly large quantities of water.
Safety	All electric cooker hobs feature the most modern and sophisticated safety protections: Centralised power-off function; Child-proof safety lock; Residual heat warning lights. Induction models feature the following functions: Safety System that turn off the hob in the absence of the pot; Overflow detector that automatically turns off the plate in case of liquid overflow; Automatic deactivation to prevent accidents caused by forgetfulness.
Smart fan system	Correct ventilation is essential for the induction hob to function in the best possible way. The Foster system automatically regulates the amount of ventilation to suit the temperatures reached.

Timer

Independent timer from the end-of-cooking function.

TECHNICAL DATA



GALLERY

